LED Pendant

PD51607

START FROM HERE

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- · Wear gloves at all time during this installation
- · Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Technical Support: 1-855-855-8926

Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage) or TRIAC type of dimmer for dimming application
- 120V input

- 1. Remove fixture from its original package.
- 2. Separate mounting plate (1c) from canopy (2a) by removing canopy screws with allen key (2f).
- **3.** Attach mounting plate (1c) to electrical junction box (1a) using screws provided (1e) in hardware package.
- **4.** Make sure Aircraft Cable (2e) is securely attached between canopy (2a) and mounting plate (1c).
- **5.** To change fixture height, push and hold wire gripper (2g), slide wire to desired length and then release wire gripper (2g) to secure (Remove excess wire if necessary)
- **6.** Make proper electrical connections between LED and DC driver, LED- Negative (black), LED+ Positive (White) using quick connector provided **(4b)** (See Illustation 1 and refer to diagram on driver)
- Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package and place driver (2b) inside the canopy (2a)
- **8.** Secure canopy (2a) to mounting plate (1c) with canopy screws (2f) using allen key
- **9.** Align, insert mounting hardware on back of light guide shade **(3a)** onto fixture mounting plate **(3d)**, rotate clockwise slightly to secure light guide shade



